

P.O. Box 2673 Muskogee, OK 74402 800.247.9433 — Phone 918.686.8785 - Fax

WWW.WELDRIL.COM



WelDril Products is reknowned among those who work in the oil patch for its commitment to providing outstanding products and services to its customers. In keeping with that commitment, WelDril has developed a superior lost circulation / extender additive, **Kol**-Seal.™

Kol-Seal[™] is a lightweight granular solid with a specific particle-size distribution for maximum bridging efficiency. It provides an economical cementing system with low-density lost circulation control and a superior scouring action.

Kol-Seal™ Recommended Uses:

- · Extender and scouring agent
- Preparation of lightweight, high-yield cementitious slurries for restoring circulation

Other WelDril LCM Products:

SuprSeal*
SEVERE LOST CIRCULATION MATERIAL

Pol-E-Flake

Performance Benefits:

- Insoluble in oil
- Does not soften at high temperatures
- Does not appreciably change the thickening time of cement
- Provides slurries that have higher compressive strengths at all ages, compared to slurries containing other lostcirculation and extending additives
- Compatible with most other cement additives
- Does not require complicated mixing equipment or procedures

Cost Benefits:

· Competitive pricing

Customer Service Benefits:

- WelDril is known for providing exemplary service
- WelDril orders are readied for shipment the same day they are received

Available Product Information:

- Product description & recommended use
- · Material Safety Data Sheet

Physical Properties

Absolute Density: 80.8 lb./cubic ft.

Absolute Volume occupied by 1 lb.: 0.0926 gal.

Specific Gravity: 1.30 Water Requirement: 1 gal./25 lb.

Melting Point: Greater than 1,000 degrees F